FR 7096 SCC GN | Full Extension Progressive Action Drawer Slide

Specifications

- bottom mount
- 24.0 mm / 0.94 in
- dynamic up to 120 kg / 265 lbs
- solid synthetic rollers
- stainless steel 1.4509 / 441
- -25 °C to +80 °C
  -13 °F to +176 °F

Characteristics

- high lateral stability
- ideal running characteristic and smoothness of running through integrated progressive action
- integrated safety clip
- dual-sided captive profile
- synthetic stop
- self-closing
- available as heat-resistant version up to +110 °C (+230 °F)
- Easy Close Device (ECD) can be ordered optionally

Mounting Type

- cabinet profile with screw holes and drawer profile without holes
- narrow drawer profile for standard serving pans

Dimensions



Length		Extension		Weight		Item No.	Item No.
				per set		PU 1	PU 2
mm	inch	mm	inch	kg	lbs		
400	15.75	385	15.16	3.24	7.14	* 1303381002	* 1303381602
450	17.72	435	17.13	3.70	8.16	* 1303391002	* 1303391602
500	19.69	485	19.09	4.13	9.11	* 1303401002	* 1303401602
550	21.65	535	21.06	4.57	10.08	* 1303411002	* 1303411602
600	23.62	585	23.03	5.03	11.09	* 1303421002	* 1303421602
650	25.59	635	25.00	5.48	12.08	* 1303431002	* 1303431602
700	27.56	685	26.97	5.93	13.07	* 1303441002	* 1303441602
750	29.53	735	28.94	6.38	14.07	* 1303451002	* 1303451602

Packing Unit * on request

PU 1 – Sets per Box: 400 to 500 mm: **4** | 550 to 750 mm: **2**
PU 2 – 20 Sets, all 6 profiles individually packaged, 6 boxes
(2 x 10 cabinet profiles LEFT/RIGHT, 2 x 10 middle profiles LEFT/RIGHT, 2 x 20 drawer profiles LEFT/RIGHT)