FR 7096 SCC OE | Over Extension Progressive Action Drawer Slide

Specifications

- bottom mount
- 24.0 mm / 0.94 in
- dynamic up to 95 kg / 209 lbs
- solid synthetic rollers
- stainless steel 1.4509 / 441
- -25 °C to +80 °C
  -13 °F to +176 °F

Characteristics

- high lateral stability
- ideal running characteristic and smoothness of running through integrated progressive action
- integrated safety clip
- dual-sided captive profile
- synthetic stop
- self-closing
- available as heat-resistant version up to +110 °C (+230 °F)
- Easy Close Device (ECD) can be ordered optionally

Mounting Type

- cabinet and drawer profiles with screw holes

Dimensions



Length		Extension		Weight		Item No.	Item No.
				per set		PU 1	PU 2
mm	inch	mm	inch	kg	lbs		
400	15.75	460	18.11	3.40	7.50	▸ 1303251002	▸ 1303251602
450	17.72	510	20.08	3.86	8.51	▸ 1303261002	▸ 1303261602
500	19.69	560	22.05	4.32	9.52	▸ 1303271002	▸ 1303271602
550	21.65	610	24.02	4.79	10.56	▸ 1303281002	▸ 1303281602
600	23.62	660	25.98	5.26	11.60	▸ 1303291002	▸ 1303291602
650	25.59	710	27.95	5.73	12.63	▸ 1303301002	▸ 1303301602
700	27.56	760	29.92	6.20	13.67	▸ 1303311002	▸ 1303311602
750	29.53	810	31.89	6.67	14.70	▸ 1303321002	▸ 1303321602

Packing Unit ▸ in stock

PU 1 – Sets per Box: 400 to 500 mm: **4** | 550 to 750 mm: **2**
PU 2 – 20 Sets, all 6 profiles individually packaged, 6 boxes
(2 x 10 cabinet profiles LEFT/RIGHT, 2 x 10 middle profiles LEFT/RIGHT, 2 x 20 drawer profiles LEFT/RIGHT)