FR 7096 SCC | Full Extension Progressive Action Drawer Slide

Specifications

- bottom mount
- 24.0 mm / 0.94 in
- dynamic up to 120 kg / 265 lbs
- solid synthetic rollers
- stainless steel 1.4509 / 441
- -25 °C to +80 °C
  -13 °F to +176 °F

Characteristics

- high lateral stability
- ideal running characteristic and smoothness of running through integrated progressive action
- integrated safety clip
- dual-sided captive profile
- synthetic stop
- self-closing
- available as heat-resistant version up to +110 °C (+230 °F)
- Easy Close Device (ECD) can be ordered optionally

Mounting Type

- cabinet and drawer profiles with screw holes

Dimensions



Length		Extension		Weight		Item No.	Item No.
				per set		PU 1	PU 2
mm	inch	mm	inch	kg	lbs		
400	15.75	385	15.16	3.38	7.45	▸ 1303121002	▸ 1303121602
450	17.72	435	17.13	3.84	8.47	▸ 1303131002	▸ 1303131602
500	19.69	485	19.09	4.30	9.48	▸ 1303141002	▸ 1303141602
550	21.65	535	21.06	4.76	10.49	▸ 1303151002	▸ 1303151602
600	23.62	585	23.03	5.23	11.53	▸ 1303161002	▸ 1303161602
650	25.59	635	25.00	5.70	12.57	▸ 1303171002	▸ 1303171602
700	27.56	685	26.97	6.17	13.60	▸ 1303181002	▸ 1303181602
750	29.53	735	28.94	6.64	14.64	▸ 1303191002	▸ 1303191602

Packing Unit ▸ in stock

PU 1 – Sets per Box: 400 to 500 mm: **4** | 550 to 750 mm: **2**
PU 2 – 20 Sets, all 6 profiles individually packaged, 6 boxes
(2 x 10 cabinet profiles LEFT/RIGHT, 2 x 10 middle profiles LEFT/RIGHT, 2 x 20 drawer profiles LEFT/RIGHT)