FR 795 SCC OE | Over Extension Progressive Action Drawer Slide

Specifications

- side mount
- 18.0 mm / 0.71 in.
- dynamic up to 60 kg / 132 lbs.
- solid synthetic rollers
- stainless steel 1.4509 / 441
- -25 °C to +80 °C
  -13 °F to +176 °F

Characteristics

- high lateral stability
- ideal running characteristic and smoothness of running through integrated progressive action
- integrated safety clip
- dual-sided captive profile
- synthetic stop
- self-closing
- compatible with regular extension drawer slide FR 1052 SCC
- available as heat-resistant version up to +110 °C (+230 °F)
- Easy Close Device (ECD) can be ordered optionally

Mounting Type

- cabinet and drawer profile with screw holes

Dimensions



Length		Extension		Weight		Item No.	Item No.
				per set		PU 1	PU 2
mm	inch	mm	inch	kg	lbs.		
300	**11.81**	335	13.19	1.34	2.96	**70330**	**70330GV**
350	**13.78**	410	16.14	1.50	3.31	**70331**	**70331GV**
400	**15.75**	460	18.11	1.68	3.71	**70332**	**70332GV**
450	**17.72**	510	20.08	1.93	4.26	**70333**	**70333GV**
500	**19.69**	560	22.05	2.16	4.76	**70334**	**70334GV**
550	**21.65**	610	24.02	2.39	5.26	**70335**	**70335GV**
600	**23.62**	660	25.98	2.62	5.78	**70336**	**70336GV**
650	**25.59**	710	27.95	2.87	6.32	**70337**	**70337GV**
700	**27.56**	760	29.92	3.10	6.83	**70338**	**70338GV**
750	**29.53**	810	31.89	3.34	7.36	**70339**	**70339GV**

Packing Unit

PU 1 – Sets assembled per Box, all Lengths: 5
PU 2 – 50 Sets, all 6 profiles individually packaged, 10 boxes
(4 x 25 cabinet profiles LEFT/RIGHT, 4 x 25 middle profiles LEFT/RIGHT, 2 x 50 drawer profiles LEFT/RIGHT)