FR 7095 SCC OE | Over Extension Progressive Action Drawer Slide

Specifications

- side mount
- 24.0 mm / 0.94 in
- dynamic up to 95 kg / 209 lbs
- solid synthetic rollers
- stainless steel 1.4509 / 441
- -25 °C to +80 °C
  -13 °F to +176 °F

Characteristics

- high lateral stability
- ideal running characteristic and smoothness of running through integrated progressive action
- integrated safety clip
- dual-sided captive profile
- synthetic stop
- self-closing
- available as heat-resistant version up to +110 °C (+230 °F)
- Easy Close Device (ECD) can be ordered optionally

Mounting Type

- cabinet and drawer profiles with screw holes

Dimensions



Length		Extension		Weight		Item No.	Item No.
				per set		PU 1	PU 2
mm	inch	mm	inch	kg	lbs		
400	15.75	460	18.11	3.20	7.05	1302211002	1302211602
450	17.72	510	20.08	3.64	8.02	1302221002	1302221602
500	19.69	560	22.05	4.07	8.97	1302231002	1302231602
550	21.65	610	24.02	4.51	9.94	1302241002	1302241602
600	23.62	660	25.98	4.95	10.91	1302251002	1302251602
650	25.59	710	27.95	5.40	11.90	1302261002	1302261602
700	27.56	760	29.92	5.84	12.87	1302271002	1302271602
750	29.53	810	31.89	6.28	13.85	1302281002	1302281602

Packing Unit ▸ in stock

PU 1 – Sets per Box: 400 to 500 mm: **4** | 550 to 750 mm: **2**
PU 2 – 20 Sets, all 6 profiles individually packaged, 6 boxes
(2 x 10 cabinet profiles LEFT/RIGHT, 2 x 10 middle profiles LEFT/RIGHT, 2 x 20 drawer profiles LEFT/RIGHT)

Fulterer