FR 795 SCC OE SMT | Over Extension Progressive Action Drawer Slide

Specifications

- side mount
- 18.0 mm / 0.71 in.
- dynamic up to 60 kg / 132 lbs.
- solid synthetic rollers
- stainless steel 1.4509 / 441
- -25 °C to +80 °C
  -13 °F to +176 °F

Characteristics

- high lateral stability
- ideal running characteristic and smoothness of running through integrated progressive action
- integrated safety clip
- dual-sided captive profile
- synthetic stop
- self-closing
- compatible with regular extension drawer slide FR 1052 SCC SMT
- available as heat-resistant version up to +110 °C (+230 °F)
- Easy Close Device (ECD) can be ordered optionally, from length 350 mm (13.78 in.)

Mounting Type

- cabinet profile with bayonet mounting tabs and safety nose
- drawer profile without screw holes
- tool-less quick assembly of the cabinet profile

Dimensions

Length		Extension		Weight		Item No.	Item No.
				per set		PU 1	PU 2
mm	inch	mm	inch	kg	lbs.		
300	11.81	335	13.19	1.38	3.04	▸ 1024251002	1024251602
350	13.78	385	15.16	1.46	3.22	▸ 1024391002	▸ 1024391602
400	15.75	460	18.11	1.69	3.73	▸ 1024541002	▸ 1024541602
450	17.72	510	20.08	1.93	4.26	▸ 1024691002	▸ 1024691602
500	19.69	560	22.05	2.16	4.76	▸ 1024841002	▸ 1024841602
550	21.65	610	24.02	2.40	5.28	▸ 1025011002	▸ 1025011602
600	23.62	660	25.98	2.64	5.82	▸ 1025161002	▸ 1025161602
650	25.59	710	27.95	2.87	6.33	▸ 1025301002	▸ 1025301602
700	27.56	760	29.92	3.11	6.86	▸ 1028711002	▸ 1028711602
750	29.53	810	31.89	3.37	7.43	1028391002	1028391602

Packing Unit ▸ in stock

PU 1 – Sets assembled per Box, all Lengths: 5
PU 2 – 50 Sets, all 6 profiles individually packaged, 10 boxes
(4 x 25 cabinet profiles LEFT/RIGHT, 4 x 25 middle profiles LEFT/RIGHT, 2 x 50 drawer profiles LEFT/RIGHT)