FR 795 SCC SMT | Full Extension Progressive Action Drawer Slide

Specifications

- side mount
- 18.0 mm / 0.71 in.
- dynamic up to 70 kg / 154 lbs.
- solid synthetic rollers
- stainless steel 1.4509 / 441
- -25 °C to +80 °C
  -13 °F to +176 °F

Characteristics

- high lateral stability
- integrated safety clip
- dual-sided captive profile
- synthetic stop
- self-closing
- compatible with regular extension drawer slide FR 1052 SCC SMT
- available as heat-resistant version up to +110 °C (+230 °F)
- Easy Close Device (ECD) can be ordered optionally

Mounting Type

- cabinet profile with bayonet mounting tabs and safety nose
- drawer profile without screw holes
- tool-less quick assembly of the cabinet profile

Dimensions



Length		Extension		Weight		Item No.	Item No.
				per set		PU 1	PU 2
mm	inch	mm	inch	kg	lbs.		
300	**11.81**	285	11.22	1.37	3.01	**70440**	**70440GV**
350	**13.78**	335	13.19	1.44	3.19	**70441**	**70441GV**
400	**15.75**	385	15.16	1.68	3.70	**70442**	**70442GV**
450	**17.72**	435	17.13	1.92	4.23	**70443**	**70443GV**
500	**19.69**	485	19.09	2.14	4.73	**70444**	**70444GV**
550	**21.65**	535	21.06	2.38	5.25	**70445**	**70445GV**
600	**23.62**	585	23.03	2.62	5.79	**70446**	**70446GV**
650	**25.59**	635	25.00	2.86	6.30	**70447**	**70447GV**
700	**27.56**	685	26.97	3.10	6.83	**70448**	**70448GV**
750	**29.53**	735	28.94	3.36	7.40	**70449**	**70449GV**

Packing Unit

PU 1 – Sets assembled per Box, all Lengths: 5
PU 2 – 50 Sets, all 6 profiles individually packaged, 10 boxes
(4 x 25 cabinet profiles LEFT/RIGHT, 4 x 25 middle profiles LEFT/RIGHT, 2 x 50 drawer profiles LEFT/RIGHT)