FR 795 SCC OE SMT | Over Extension Progressive Action Drawer Slide

Specifications

- side mount
- 18.0 mm / 0.71 in.
- dynamic up to 60 kg / 132 lbs.
- solid synthetic rollers
- stainless steel 1.4509 / 441
- -25 °C to +80 °C
  -13 °F to +176 °F

Characteristics

- high lateral stability
- integrated safety clip
- dual-sided captive profile
- synthetic stop
- self-closing
- compatible with regular extension drawer slide FR 1052 SCC SMT
- available as heat-resistant version up to +110 °C (+230 °F)
- Easy Close Device (ECD) can be ordered optionally

Mounting Type

- cabinet profile with bayonet mounting tabs and safety nose
- drawer profile without screw holes
- tool-less quick assembly of the cabinet profile

Dimensions



Length		Extension		Weight		Item No.	Item No.
				per set		PU 1	PU 2
mm	inch	mm	inch	kg	lbs.		
300	**11.81**	335	13.19	1.38	3.04	**70450**	**70450GV**
350	**13.78**	410	16.14	1.46	3.22	**70451**	**70451GV**
400	**15.75**	460	18.11	1.69	3.73	**70452**	**70452GV**
450	**17.72**	510	20.08	1.93	4.26	**70453**	**70453GV**
500	**19.69**	560	22.05	2.16	4.76	**70454**	**70454GV**
550	**21.65**	610	24.02	2.40	5.28	**70455**	**70455GV**
600	**23.62**	660	25.98	2.64	5.82	**70456**	**70456GV**
650	**25.59**	710	27.95	2.87	6.33	**70457**	**70457GV**
700	**27.56**	760	29.92	3.11	6.86	**70458**	**70458GV**
750	**29.53**	810	31.89	3.37	7.43	**70459**	**70459GV**

Packing Unit

PU 1 – Sets assembled per Box, all Lengths: 5
PU 2 – 50 Sets, all 6 profiles individually packaged, 10 boxes
(4 x 25 cabinet profiles LEFT/RIGHT, 4 x 25 middle profiles LEFT/RIGHT, 2 x 50 drawer profiles LEFT/RIGHT)