FR 795 SCC OE | Over Extension Progressive Action Drawer Slide

Specifications

- side mount
- 18.0 mm / 0.71 in.
- dynamic up to 60 kg / 132 lbs.
- solid synthetic rollers
- stainless steel 1.4509 / 441
- -25 °C to +80 °C
  -13 °F to +176 °F

Characteristics

- high lateral stability
- ideal running characteristic and smoothness of running through integrated progressive action
- integrated safety clip
- dual-sided captive profile
- synthetic stop
- self-closing
- compatible with regular extension drawer slide FR 1052 SCC
- available as heat-resistant version up to +110 °C (+230 °F)
- Easy Close Device (ECD) can be ordered optionally, from length 350 mm (13.78 in.)

Mounting Type

- cabinet and drawer profiles with screw holes

Dimensions



Length		Extension		Weight		Item No.	Item No.
				per set		PU 1	PU 2
mm	inch	mm	inch	kg	lbs.		
300	11.81	335	13.19	1.34	2.96	▸ 1024231002	1024231602
350	13.78	385	15.16	1.50	3.31	▸ 1024371002	1024371602
400	15.75	460	18.11	1.68	3.71	1024521002	1024521602
450	17.72	510	20.08	1.93	4.26	▸ 1024671002	▸ 1024671602
500	19.69	560	22.05	2.16	4.76	1024821002	1024821602
550	21.65	610	24.02	2.39	5.26	▸ 1024991002	▸ 1024991602
600	23.62	660	25.98	2.62	5.78	1025141002	1025141602
650	25.59	710	27.95	2.87	6.32	▸ 1025281002	▸ 1025281602
700	27.56	760	29.92	3.10	6.83	▸ 1025421002	1025421602
750	29.53	810	31.89	3.34	7.36	1028371002	1028371602

Packing Unit ▸ in stock

PU 1 – Sets assembled per Box, all Lengths: 5
PU 2 – 50 Sets, all 6 profiles individually packaged, 10 boxes
(4 x 25 cabinet profiles LEFT/RIGHT, 4 x 25 middle profiles LEFT/RIGHT, 2 x 50 drawer profiles LEFT/RIGHT)