FR 795 SCC OE DMT | Over Extension Progressive Action Drawer Slide

Specifications

- side mount
- 18.0 mm / 0.71 in.
- dynamic up to 60 kg / 132 lbs.
- solid synthetic rollers
- stainless steel 1.4509 / 441
- -25 °C to +80 °C
  -13 °F to +176 °F

Characteristics

- high lateral stability
- ideal running characteristic and smoothness of running through integrated progressive action
- integrated safety clip
- dual-sided captive profile
- synthetic stop
- self-closing
- available as heat-resistant version up to +110 °C (+230 °F)
- Easy Close Device (ECD) can be ordered optionally, from length 350 mm (13.78 in.)

Mounting Type

- cabinet and drawer profiles with bayonet mounting tabs and safety nose
- tool-less quick assembly of cabinet and drawer profiles

Dimensions



Length		Extension		Weight		Item No.	Item No.
				per set		PU 1	PU 2
mm	inch	mm	inch	kg	lbs.		
300	**11.81**	335	13.19	1.38	3.04	**1024281002**	**1024281602**
350	**13.78**	385	15.16	1.46	3.22	**1024421002**	▸ **1024421602**
400	**15.75**	460	18.11	1.69	3.73	**1024571002**	**1024571602**
450	**17.72**	510	20.08	1.93	4.26	**1024731002**	▸ **1024731602**
500	**19.69**	560	22.05	2.16	4.76	**1024871002**	▸ **1024871602**
550	**21.65**	610	24.02	2.40	5.28	**1025051002**	▸ **1025051602**
600	**23.62**	660	25.98	2.64	5.82	**1025191002**	**1025191602**
650	**25.59**	710	27.95	2.87	6.33	**1025331002**	▸ **1025331602**
700	**27.56**	760	29.92	3.11	6.86	**1028281002**	**1028281602**
750	**29.53**	810	31.89	3.37	7.43	**1028411002**	**1028411602**

Packing Unit ▸ in stock

PU 1 – Sets assembled per Box, all Lengths: 5
PU 2 – 50 Sets, all 6 profiles individually packaged, 10 boxes
(4 x 25 cabinet profiles LEFT/RIGHT, 4 x 25 middle profiles LEFT/RIGHT, 2 x 50 drawer profiles LEFT/RIGHT)